



DECLARATION OF PERFORMANCE

No

1343-CPR-M 545-11_EN

EN

1. Unique identification code of the product-type: **DEWALT PURE150-PRO injection resin with anchor rod for concrete**
2. Intended use/es: **Bonded anchor for diamond coring for use in uncracked concrete**
3. Manufacturer: **DEWALT
Black & Decker Straße 40
65510 Idstein, Germany**
4. Authorised representative: **not applicable**
5. System/s of AVCP: **System 1**
6. European Assessment Document: **ETAG 001 Part 5, April 2013 used as EAD**
 European Technical Assessment: **ETA-12/0606 (23.04.2015)**
 Technical Assessment Body: **DIBt - Deutsches Institut für Bautechnik Berlin**
 Notified body/ies: **NB 1343 MPA Darmstadt**

7. Declared performance/s:
 Mechanical resistance and stability (BWR 1)

Essential Characteristics	Performance
Characteristic resistance for design according to TR 029	See Annex C1 to C6
Char. resistance for design acc. to CEN/TS 1992-4:2009	See Annex C7 to C12
Displacements under tension and shear loads	See Annex C13 to C15

Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Resistance to fire	No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Karl Evans
Vice President
Professional Power Tools EANZ

Idstein, 05.07.2018

Dr.-Ing. Philipp Mahrenholtz
Senior Engineering Manager



This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.

DoP No. 1343-CPR-M 545-11 (R5)